

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number
WO 2005/005126 A3

- (51) International Patent Classification⁷: **B29C 45/14** (74) Agent: **KLINGSEISEN, Franz**; Bräuhäusstrasse 4, 80331 München (DE).
- (21) International Application Number: PCT/EP2004/007687 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 12 July 2004 (12.07.2004) (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 103 31 519.5 11 July 2003 (11.07.2003) DE
- (71) Applicant (for all designated States except US): **HEKUMA GMBH** [DE/DE]; Freisinger Str. 3b, 85386 Eching (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KNÖPFLER, Kurt** [DE/DE]; Diessener Str. 2, 80638 München (DE).

[Continued on next page]

(54) Title: HANDLING SYSTEM FOR AN INJECTION MOLDING MACHINE AND METHOD FOR INSERTING AN INSERT INTO THE INJECTION MOLD



(57) Abstract: A handling system for an injection molding machine is presented wherein an application, for example a label, is inserted in the mold cavity (105) of an injection molding tool (104) before injection molding, when for example a beaker having the label (1) on the outer circumference is fabricated by injection molding, wherein a preform means (8) for the label (1) is provided outside the injection molding tool, has a feeder means (3, 4) for the label and a preform (5) into which the label is introduced by the feeder means, and is thus preformed to the shape in which it is to be inserted in the injection mold (105), and a transfer means (302) removes the preformed label from the preform (5) and delivers it to the injection mold (105), wherein the preform (5) is decouplable from the feeder means (3, 4) and moveable into a position different from it.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
9 June 2005

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.